



## Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Fabric/Acrylic |
| Application       | Flush Mount    |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

## Standard Selection

|         |                                              |
|---------|----------------------------------------------|
| Voltage | 120V Triac dimming                           |
| CCT     | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

## Fabric Finish

- |                                          |                                      |
|------------------------------------------|--------------------------------------|
| <input type="checkbox"/> Black Linen     | <input type="checkbox"/> Jute Linen  |
| <input type="checkbox"/> Chocolate Linen | <input type="checkbox"/> White Linen |
| <input type="checkbox"/> Grey Linen      |                                      |

## CCT Options

|     |                                              |
|-----|----------------------------------------------|
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |
|-----|----------------------------------------------|

## Options

| Size    | Dimensions    | Wattage  | Voltage                                                                                                         | Lumens         |
|---------|---------------|----------|-----------------------------------------------------------------------------------------------------------------|----------------|
| RFNB-12 | D:12" H:4"    | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNB-15 | D:15" H:4"    | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNB-19 | D:19" H:5.25" | 15/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/3900 |
| RFNB-24 | D:24" H:8"    | 15/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |
| RFNB-30 | D:30" H:8"    | 25/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/4550/5200 |
| RFNB-36 | D:36" H:8"    | 35/40/50 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4550/5200/6500 |

## Options

OS - Occupancy Sensor  
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)