



### Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
CCT	3000K

### Fabric Finish

- White Linen

### Finish Options

- Brushed Nickel Trim With Fabric Lens

### CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
RFU-12	D:11.7" H:5"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming ) / DV (120V-277V (non dimming))	1300/2340/3250
RFU-15	D:14.5" H:5"	15/24	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming ) / DV (120V-277V (non dimming))	1950/3120
RFU-17	D:17.7" H:3"	15/25/32	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming ) / DV (120V-277V (non dimming))	1950/3250/4160
RFU-18	D:17.7" H:5"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming ) / DV (120V-277V (non dimming))	1950/3250/4550

### Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)