







Properties		
Base Construction	Cold-rolled Steel	
Lens	Acrylic	
Application	Flush Mount	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V Triac dimming	
Finish	Brushed Nickel	
CCT	3000K	
<b>Finish Options</b>		
□ Black	☐ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	□ White	
<b>CCT Options</b>		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUB-10	D:10.5" H:2.6"	10/17	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/2210
RFUB-15	D:15" H:2.6"	10/15/23	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2990
RFUB-19	D:19" H:2.6"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/3250/4550

## Options

OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com