





Properties	
Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	Gold/Brass
CCT	3000K
Finish Options	
□ Black	□ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	
CCT	3000K/4000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUBB-14	D:14.6" H:3"	10/12/15/2 0/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1560/1950/260 0/3250
RFUBB-16	D:16" H:3"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/2340/3250
RFUBB-18	D:17.8" H:3"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
RFUBB-21	D:20.5" H:3"	15/20/25/3 2	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250/416 0

Not seeing what you're looking for?

Contact us!

info@asllighting.com