



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Gold/Brass
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- | | |
|---|-------------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White |

CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUBB-14	D:14.6" H:3"	10/12/15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1560/1950/2600/3250
RFUBB-16	D:16" H:3"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2340/3250
RFUBB-21	D:20.5" H:3"	15/20/25/30/2	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250/4160

Not seeing what you're looking for?

Contact us!

info@asllighting.com