





# **Properties**

Cold-rolled Steel	Base Construction
Acrylic	Lens
Flush Mount	Application
Damp	Location
80	CRI
50,000	Life Hours
Integrated LED	Light Source

# **Standard Selection**

Voltage 120V-277V (non dimm	
CCT	3000K

#### **Fabric Finish**

☐ White Linen

### **Finish Options**

☐ Brushed Nickel Trim With Fabric Lens

# **CCT Options**

CCT

2700K/3000K/3500k/4000K/5000K

### **Options**

Size	Dimensions	Wattage	Voltage	Lumens
RFUY-12	D:12" H:5"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/2340/3250
RFUY-16	D:15.4" H:5.2"	10/15/24/3 0	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/3120/390 0
RFUY-18	D:18.5" H:5.7"	15/20/25/3 5	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250/455 0

### Options

EMG - Emergency
OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com