



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Acrylic        |
| Application       | Flush Mount    |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                              |
|---------|------------------------------|
| Voltage | 120V Triac dimming           |
| Finish  | Black/Gold                   |
| CCT     | 3CCT - 3000K / 3500K / 4000K |

### Finish Options

- ☐ Black
 ☐ ORB
 ☐ Bronze
 ☐ White
 ☐ Brushed Nickel
 ☐ Black/Gold
 ☐ Gold/Brass

### CCT Options

CCT 3CCT - 3000K / 3500K / 4000K/5CCT - 2700K / 3000K / 3500K / 4000K / 5

### Options

| Size     | Dimensions | Wattage     | Voltage                                                                                                           | Lumens              |
|----------|------------|-------------|-------------------------------------------------------------------------------------------------------------------|---------------------|
| ROSTB-13 | D:13" H:4" | 10/15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600/3250 |

### Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)