





Properties Cold-rolled Steel **Base Construction** Lens Acrylic Flush Mount Application Location Damp CRI 80 Life Hours 50,000 Light Source Integrated LED **Standard Selection** 120V-277V (non dimming) Voltage Finish **Brushed Nickel** CCT 3000K **Finish Options** □ Black ☐ Gold/Brass \square Bronze □ ORB ☐ Brushed Nickel \square White **CCT Options** CCT 2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
WFR-14	D:14.8" H:4"	15/24	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120
WFR-17	D:16.5" H:4.5"	15/24/28	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120/3640
WFR-19	D:19" H:4.5"	15/24/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120/4550

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com