







| Properties | | |
|--------------------|-------------------------------|--|
| Base Construction | Cold-rolled Steel | |
| Lens | Acrylic | |
| Application | Flush Mount | |
| Location | Damp | |
| CRI | 80 | |
| Life Hours | 50,000 | |
| Light Source | Integrated LED | |
| Standard Selection | | |
| Voltage | 120V-277V (non dimming) | |
| Finish | Brushed Nickel | |
| CCT | 3000K | |
| Finish Options | | |
| □ Black | ☐ Gold/Brass | |
| □ Bronze | □ ORB | |
| ☐ Brushed Nickel | □ White | |
| CCT Options | | |
| CCT | 2700K/3000K/3500k/4000K/5000K | |

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|--------------|----------|---|----------------|
| WFTB-14 | D:14" H:2.5" | 10/17 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2210 |
| WFTB-16 | D:16" H:2.5" | 10/17/23 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2210/2990 |
| WFTB-18 | D:18" H:2.5" | 17/23/35 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2210/2990/4550 |
| WFTB-24 | D:24" H:2.5" | 23/35/46 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2990/4550/5980 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com