



Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2101-23	D:23.6" H:1.3" MH:59"	40	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	5200
C2101-35	D:35.6" H:1.3" MH:59"	50	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	6500
C2101-47	D:47" H:1.3" MH:59"	80	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	10400
C2101-59	D:59" H:1.3" MH:59"	100	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	13000
C2101-78	D:78" H:1.3" MH:59"	120	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	15600
C2101-118	D:118" H:1.3" MH:59"	200	DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	26000

Not seeing what you're looking for?

Contact us!

info@asllighting.com