



Properties

| | |
|-------------------|----------------|
| Base Construction | Aluminum |
| Lens | Acrylic |
| Application | Pendant |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | White |
| CCT | 4000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|-----------|--------------------------|---------|---------------------------------------------------------------------------------------|--------|
| C2101-23 | D:23.6" H:1.3" MH:59" | 40 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 5200 |
| C2101-35 | D:35.6" H:1.3" MH:59" | 50 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 6500 |
| C2101-47 | D:47" H:1.3" MH:59" | 80 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 10400 |
| C2101-78 | D:78" H:1.3" MH:59" | 120 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 15600 |
| C2101-118 | D:118" H:1.3" MH:59" | 200 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 26000 |
| C2101-196 | D:196" H:1.3" MH:59" | 400 | DV (120V-277V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) | 52000 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com