



Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	Up/Down

Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2102-23	D:23.6" H:2.7"	65	DV (120V-277V (non dimming))	8450
C2102-35	D:35.6" H:2.7"	80	DV (120V-277V (non dimming))	10400
C2102-47	D:47" H:2.7"	120	DV (120V-277V (non dimming))	15600
C2102-59	D:59" H:2.7"	135	DV (120V-277V (non dimming))	17550
C2102-78	D:78" H:2.7"	150	DV (120V-277V (non dimming))	19500
C2102-118	D:118" H:2.7"	300	DV (120V-277V (non dimming))	39000
C2102-196	D:196" H:2.7"	480	DV (120V-277V (non dimming))	62400

Not seeing what you're looking for?

Contact us!

info@asllighting.com