



Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	OO OUTER EMITTING

Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

Finish Options

- | | |
|---|-------------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White |

CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2105-23	D:23.6" H:1.4" W:1.3" MH:59"	32	DV (120V-277V (non dimming))	4160
C2105-35	D:35.4" H:1.4" W:1.3" MH:59"	40	DV (120V-277V (non dimming))	5200
C2105-47	D:47" H:1.4" W:1.3" MH:59"	70	DV (120V-277V (non dimming))	9100
C2105-59	D:59" H:1.4" W:1.3" MH:59"	80	DV (120V-277V (non dimming))	10400

Not seeing what you're looking for?

Contact us!

info@asllighting.com