



### Properties

|                   |                  |
|-------------------|------------------|
| Base Construction | Aluminum         |
| Lens              | Acrylic          |
| Application       | Pendant          |
| Location          | Dry              |
| CRI               | 80               |
| Life Hours        | 50,000           |
| Light Source      | Integrated LED   |
| Light Direction   | O OUTER EMITTING |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | White                   |
| CCT     | 4000K                   |

### Finish Options

- ☐ Black
☐ Gold/Brass
- ☐ Bronze
☐ ORB
- ☐ Brushed Nickel
☐ White

### CCT Options

|     |                         |
|-----|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|-----|-------------------------|

### Options

| Size     | Dimensions     | Wattage | Voltage                      | Lumens |
|----------|----------------|---------|------------------------------|--------|
| C2105-23 | D:23.6" H:1.4" | 32      | DV (120V-277V (non dimming)) | 4160   |
| C2105-35 | D:35.4" H:1.4" | 40      | DV (120V-277V (non dimming)) | 5200   |
| C2105-47 | D:47" H:1.4"   | 70      | DV (120V-277V (non dimming)) | 9100   |
| C2105-59 | D:59" H:1.4"   | 80      | DV (120V-277V (non dimming)) | 10400  |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)