



### Properties

Base Construction	Aluminum
Lens	Polyethylene
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	OO OUTER EMITTING

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

### Finish Options

- White

### CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
C2106-15	D:15.7" H:2.6" MH:59"	25	DV (120V-277V (non dimming))	3250
C2106-23	D:23" H:2.6" MH:59"	36	DV (120V-277V (non dimming))	4680
C2106-35	D:35" H:2.6" MH:59"	60	DV (120V-277V (non dimming))	7800
C2106-47	D:47" H:2.6" MH:59"	80	DV (120V-277V (non dimming))	10400
C2106-59	D:59" H:2.6" MH:59"	100	DV (120V-277V (non dimming))	13000
C2106-70	D:70" H:2.6" MH:59"	120	DV (120V-277V (non dimming))	15600

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)