



### Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	OO OUTER EMITTING

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

### Finish Options

- White

### CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
C2107-15	D:15.7" H:2.8" MH:59"	15	DV (120V-277V (non dimming))	1950
C2107-23	D:23" H:2.8" MH:59"	25	DV (120V-277V (non dimming))	3250
C2107-31	D:31" H:2.8" MH:59"	35	DV (120V-277V (non dimming))	4550
C2107-39	D:39.4" H:2.8" MH:59"	45	DV (120V-277V (non dimming))	5850
C2107-47	D:47" H:2.8" MH:59"	50	DV (120V-277V (non dimming))	6500
C2107-59	D:59" H:2.8" MH:59"	60	DV (120V-277V (non dimming))	7800

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)