



### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Aluminum          |
| Lens              | Acrylic           |
| Application       | Pendant           |
| Location          | Dry               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |
| Light Direction   | OO OUTER EMITTING |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | White                   |
| CCT     | 4000K                   |

### Finish Options

- White

### CCT Options

|     |                         |
|-----|-------------------------|
| CCT | 3000K/3500k/4000K/5000K |
|-----|-------------------------|

### Options

| Size     | Dimensions               | Wattage | Voltage                      | Lumens |
|----------|--------------------------|---------|------------------------------|--------|
| C2108-15 | D:15.7" H:2.8"<br>MH:59" | 30      | DV (120V-277V (non dimming)) | 3900   |
| C2108-31 | D:31" H:2.8"<br>MH:59"   | 60      | DV (120V-277V (non dimming)) | 7800   |
| C2108-39 | D:39.4" H:2.8"<br>MH:59" | 80      | DV (120V-277V (non dimming)) | 10400  |
| C2108-47 | D:47" H:2.8"<br>MH:59"   | 90      | DV (120V-277V (non dimming)) | 11700  |
| C2108-59 | D:59" H:2.8"<br>MH:59"   | 100     | DV (120V-277V (non dimming)) | 13000  |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)