




Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP AND DOWN

Standard Selection

Voltage	120V-277V (non dimming)
Finish	ASL-002 122
CCT	4000K

Finish Options

- | | |
|--------------------------------------|--------------------------------------|
| ☐ ASL-001 141 | ☐ ASL-021 130 |
| ☐ ASL-002 122 | ☐ ASL-022 119 |
| ☐ ASL-003 120 | ☐ ASL-024 117 |
| ☐ ASL-004 123 | ☐ ASL-025 138 |
| ☐ ASL-005 107 | ☐ ASL-028 110 |
| ☐ ASL-006 106 | ☐ ASL-031 108 |
| ☐ ASL-007 145 | ☐ ASL-033 103 |
| ☐ ASL-008 129 | ☐ ASL-034 102 |
| ☐ ASL-009 140 | ☐ ASL-035 101 |
| ☐ ASL-011 135 | ☐ ASL-036 105 |
| ☐ ASL-012 133 | ☐ ASL-038 127 |
| ☐ ASL-013 111 | ☐ ASL-039 143 |
| ☐ ASL-014 144 | ☐ ASL-040 124 |
| ☐ ASL-016 104 | ☐ ASL-042 146 |
| ☐ ASL-017 147 | ☐ ASL-043 115 |
| ☐ ASL-018 125 | ☐ ASL-055 142 |
| ☐ ASL-019 126 | ☐ ASL-056 131 |
| ☐ ASL-020 128 | ☐ ASL-057 132 |

CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2126-22	L:22" W:19" H:3"	40	DV (120V-277V (non dimming))	5200
C2126-42	L:42" W:37" H:3"	80	DV (120V-277V (non dimming))	10400
C2126-63	L:63" W:56" H:3"	120	DV (120V-277V (non dimming))	15600

Not seeing what you're looking for?

Contact us!

info@asllighting.com