



Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP AND DOWN

Standard Selection

Voltage	120V-277V (non dimming)
Finish	ASL-002 122
CCT	4000K

Finish Options

- | | |
|--------------------------------------|--------------------------------------|
| <input type="checkbox"/> ASL-001 141 | <input type="checkbox"/> ASL-021 130 |
| <input type="checkbox"/> ASL-002 122 | <input type="checkbox"/> ASL-022 119 |
| <input type="checkbox"/> ASL-003 120 | <input type="checkbox"/> ASL-024 117 |
| <input type="checkbox"/> ASL-004 123 | <input type="checkbox"/> ASL-025 138 |
| <input type="checkbox"/> ASL-005 107 | <input type="checkbox"/> ASL-028 110 |
| <input type="checkbox"/> ASL-006 106 | <input type="checkbox"/> ASL-031 108 |
| <input type="checkbox"/> ASL-007 145 | <input type="checkbox"/> ASL-033 103 |
| <input type="checkbox"/> ASL-008 129 | <input type="checkbox"/> ASL-034 102 |
| <input type="checkbox"/> ASL-009 140 | <input type="checkbox"/> ASL-035 101 |
| <input type="checkbox"/> ASL-011 135 | <input type="checkbox"/> ASL-036 105 |
| <input type="checkbox"/> ASL-012 133 | <input type="checkbox"/> ASL-038 127 |
| <input type="checkbox"/> ASL-013 111 | <input type="checkbox"/> ASL-039 143 |
| <input type="checkbox"/> ASL-014 144 | <input type="checkbox"/> ASL-040 124 |
| <input type="checkbox"/> ASL-016 104 | <input type="checkbox"/> ASL-042 146 |
| <input type="checkbox"/> ASL-017 147 | <input type="checkbox"/> ASL-043 115 |
| <input type="checkbox"/> ASL-018 125 | <input type="checkbox"/> ASL-055 142 |
| <input type="checkbox"/> ASL-019 126 | <input type="checkbox"/> ASL-056 131 |
| <input type="checkbox"/> ASL-020 128 | <input type="checkbox"/> ASL-057 132 |

CCT Options

CCT	3000K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2126-22	L:22" H:3" W:19" MH:59"	40	DV (120V-277V (non dimming))	5200
C2126-42	L:42" H:3" W:37" MH:59"	80	DV (120V-277V (non dimming))	10400
C2126-63	L:63" H:3" W:56" MH:59"	120	DV (120V-277V (non dimming))	15600

Not seeing what you're looking for?

Contact us!

info@asllighting.com