



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Pendant
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Black
CCT	4000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2127P-12	D:11.8" H:2.6"	15	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950
C2127P-16	D:15.7" H:2.6"	20	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600
C2127P-20	D:18.9" H:3.7"	25	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250
C2127P-24	D:23.6" H:3.7"	40	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	5200
C2127P-35	D:35.4" H:3.7"	90	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	11700
C2127P-47	D:47.2" H:3.7"	150	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	19500

Not seeing what you're looking for?

Contact us!

info@asllighting.com