



Properties

| | |
|-------------------|----------------|
| Base Construction | Aluminum |
| Lens | Acrylic |
| Application | Pendant |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | INNER |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Black |
| CCT | 4000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------|
| CCT | 3000K/4000K/5000K |
|-----|-------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|------------------------------|---------|------------------------------|--------|
| C2138-14 | W:14" H:3.5" L:14" MH:59" | 15 | DV (120V-277V (non dimming)) | 1950 |
| C2138-23 | W:23" H:3.5" L:23" MH:59" | 36 | DV (120V-277V (non dimming)) | 4680 |
| C2138-31 | W:31" H:3.5" L:31" MH:59" | 50 | DV (120V-277V (non dimming)) | 6500 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com