



Properties

Base Construction	Aluminum And Polyester
Lens	—
Application	Pendant
Location	Dry
Light Source	E26 Lamp Base

Standard Selection

Voltage	120V Triac dimming
Finish	ASL-012 133
CCT	—
Recommended Bulb	A19*

* Bulb not included

Finish Options

- | | |
|--------------------------------------|--------------------------------------|
| ☐ ASL-001 141 | ☐ ASL-021 130 |
| ☐ ASL-002 122 | ☐ ASL-022 119 |
| ☐ ASL-003 120 | ☐ ASL-024 117 |
| ☐ ASL-004 123 | ☐ ASL-025 138 |
| ☐ ASL-005 107 | ☐ ASL-028 110 |
| ☐ ASL-006 106 | ☐ ASL-031 108 |
| ☐ ASL-007 145 | ☐ ASL-033 103 |
| ☐ ASL-008 129 | ☐ ASL-034 102 |
| ☐ ASL-009 140 | ☐ ASL-035 101 |
| ☐ ASL-011 135 | ☐ ASL-036 105 |
| ☐ ASL-012 133 | ☐ ASL-038 127 |
| ☐ ASL-013 111 | ☐ ASL-039 143 |
| ☐ ASL-014 144 | ☐ ASL-040 124 |
| ☐ ASL-016 104 | ☐ ASL-042 146 |
| ☐ ASL-017 147 | ☐ ASL-043 115 |
| ☐ ASL-018 125 | ☐ ASL-055 142 |
| ☐ ASL-019 126 | ☐ ASL-056 131 |
| ☐ ASL-020 128 | ☐ ASL-057 132 |

CCT Options

CCT	—
-----	---

Size	Dimensions	Wattage	Voltage	Lumens
C2151-17	D:17.8" H:11.8"	—	TD (120V Triac dimming)	—

Not seeing what you're looking for?

Contact us!

info@asllighting.com