



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K

### Finish Options

- |   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

### CCT Options

CCT	3000K
-----	-------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
EOIP-13	D:12.5" H:3.8"	18	ND (120V (non dimming)) / DV (120V-277V (non dimming))	2340
EOIP-15	D:15" H:3.8"	23	ND (120V (non dimming)) / DV (120V-277V (non dimming))	2990
EOIP-17	D:16.6" H:4.1"	28	ND (120V (non dimming)) / DV (120V-277V (non dimming))	3640
EOIP-19	D:18.4" H:4.1"	35	ND (120V (non dimming)) / DV (120V-277V (non dimming))	4550

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)