





Lens Application Per Location  CRI  Life Hours Light Source Integrate  Standard Selection  Voltage 120V (non dim Finish Brushed  CCT  Finish Options Black Bronze Bronze Brushed Nickel  CCT Options	Properties	
Application  CRI  Life Hours  Light Source  Standard Selection  Voltage  Finish  Finish  Brushed  CCT  Finish Options  Black  Bronze  Brushed Nickel  CCT Options	Base Construction	Cold-rolled Steel
Location  CRI  Life Hours  Light Source  Integrate  Standard Selection  Voltage  120V (non din  Finish  Brushed  CCT  Finish Options  Black  Bronze  Bronze  Brushed Nickel  CCT Options	Lens	Acrylic
CRI  Life Hours  Standard Selection  Voltage  Finish  CCT  Finish Options  Black  Bronze  Brushed Nickel  CCT Options	Application	Pendant
Life Hours  Light Source  Integrate  Standard Selection  Voltage  120V (non dim  Finish  Brushed  CCT  Finish Options  Gold/Brass Gord Bronze GORB Brushed Nickel  White	Location	Damp
Standard Selection  Voltage 120V (non dim Finish Brushed  CCT  Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	CRI	80
Standard Selection  Voltage 120V (non dim Finish Brushed  CCT  Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	Life Hours	50,000
Voltage 120V (non dim Finish Brushed  CCT  Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	Light Source	Integrated LED
Finish Brushed  CCT  Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	Standard Selection	
Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	Voltage	120V (non dimming)
Finish Options  Black Gold/Brass  Bronze ORB Brushed Nickel White  CCT Options	Finish	Brushed Nickel
□ Black □ Gold/Brass □ Bronze □ ORB □ Brushed Nickel □ White  CCT Options	CCT	3000K
□ Bronze □ ORB □ Brushed Nickel □ White  CCT Options	Finish Options	
□ Brushed Nickel □ White  CCT Options	□ Black	☐ Gold/Brass
CCT Options	□ Bronze	□ ORB
	☐ Brushed Nickel	□ White
CCT	CCT Options	
	CCT	3000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
EOIP-13	D:12.5" H:3.8"	18	ND (120V (non dimming)) / DV (120V-277V (non dimming))	2340
EOIP-15	D:15" H:3.8"	23	ND (120V (non dimming)) / DV (120V-277V (non dimming))	2990
EOIP-17	D:16.6" H:4.1"	28	ND (120V (non dimming)) / DV (120V-277V (non dimming))	3640
EOIP-19	D:18.4" H:4.1"	35	ND (120V (non dimming)) / DV (120V-277V (non dimming))	4550

Not seeing what you're looking for?

Contact us!

info@asllighting.com