



Properties

| | |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Acrylic |
| Application | Pendant |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Gold/Brass
- Bronze
- ORB
- Brushed Nickel
- White

CCT Options

| | |
|-----|-------|
| CCT | 3000K |
|-----|-------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|----------------|---------|--|--------|
| EOIP-13 | D:12.5" H:3.8" | 18 | DV (120V-277V (non dimming)) / ND (120V (non dimming)) | 2340 |
| EOIP-15 | D:15" H:3.8" | 23 | DV (120V-277V (non dimming)) / ND (120V (non dimming)) | 2990 |
| EOIP-17 | D:16.6" H:4.1" | 28 | DV (120V-277V (non dimming)) / ND (120V (non dimming)) | 3640 |
| EOIP-19 | D:18.4" H:4.1" | 35 | DV (120V-277V (non dimming)) / ND (120V (non dimming)) | 4550 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com