



### Properties

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Base Construction | Die-formed Cold-rolled Steel and Aluminum Extrusion |
| Lens              | Glass                                               |
| Application       | Mini Pendant                                        |
| Location          | Damp                                                |
| CRI               | 80                                                  |
| Life Hours        | 50,000                                              |
| Light Source      | Integrated LED                                      |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black                   |
| CCT     | 3000K                   |

### Finish Options

- |                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size   | Dimensions    | Wattage | Voltage                                                                                 | Lumens |
|--------|---------------|---------|-----------------------------------------------------------------------------------------|--------|
| RFDJ-5 | D:4.8" H:7.8" | 14      | TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1820   |
| RFDJ-6 | D:6" H:9.1"   | 17      | TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2210   |

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)