



## Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Fabric/Acrylic |
| Application       | Pendant        |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

## Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| CCT     | 3000K                   |

## Fabric Finish

- |                                          |                                      |
|------------------------------------------|--------------------------------------|
| <input type="checkbox"/> Black Linen     | <input type="checkbox"/> Jute Linen  |
| <input type="checkbox"/> Chocolate Linen | <input type="checkbox"/> White Linen |
| <input type="checkbox"/> Grey Linen      |                                      |

## Finish Options

- |                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

## CCT Options

CCT 2700K/3000K/3500k/4000K/5000K/3CCT - 3000K / 3500K / 4000K/5CCT -

## Options

| Size     | Dimensions    | Wattage  | Voltage                                                                                                         | Lumens         |
|----------|---------------|----------|-----------------------------------------------------------------------------------------------------------------|----------------|
| RFNAP-12 | D:12" H:4"    | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNAP-15 | D:15" H:4"    | 10/15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3250 |
| RFNAP-19 | D:19" H:5.25" | 15/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/3900 |
| RFNAP-24 | D:24" H:8"    | 15/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250/4550 |
| RFNAP-30 | D:30" H:8"    | 25/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/4550/5200 |
| RFNAP-36 | D:36" H:8"    | 35/40/50 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4550/5200/6500 |

## Options

EMG – Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)