



### Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V Triac dimming
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

### Fabric Finish

- Black Linen
- Chocolate Linen
- Grey Linen
- Jute Linen
- White Linen

### CCT Options

CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K
-----	--

### Options

Size	Dimensions	Wattage	Voltage	Lumens
RFNCP-12	D:12" H:4" MH:6'	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNCP-19	D:19" H:5.25" MH:6'	15/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/3900
RFNCP-24	D:24" H:8" MH:6'	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550
RFNCP-30	D:30" H:8" MH:6'	25/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/5200
RFNCP-36	D:36" H:8" MH:6'	35/40/50	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550/5200/6500

### Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)