



Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Fabric Finish

- Black Linen
- Chocolate Linen
- Grey Linen
- Jute Linen
- White Linen

CCT Options

CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K
-----	--

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFNEP-12	D:12" H:4"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNEP-15	D:15" H:4"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
RFNEP-19	D:19" H:5.25"	15/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/3900
RFNEP-24	D:24" H:8"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550
RFNEP-30	D:30" H:8"	25/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/5200
RFNEP-36	D:36" H:8"	35/40/50	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550/5200/6500

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com