



Properties

| | |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Fabric/Acrylic |
| Application | Pendant |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | White |
| CCT | 3000K |

Finish Options

White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|-----------|----------------|---------|---|--------|
| RFOBAP-16 | D:16.1" H:3.6" | 24 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3120 |
| RFOBAP-21 | D:20.8" H:3.6" | 32 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4160 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com