



Properties

Base Construction	Steel
Lens	Fabric/Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
CCT	3000K

Fabric Finish

- ☐ White Linen

Finish Options

- ☐ Brushed Nickel Trim With Fabric Lens

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUP-12	D:11.7" H:5"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1300/2340/3250
RFUP-14	D:14.5" H:3"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1950/3250
RFUP-15	D:14.5" H:5"	15/24	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1950/3120
RFUP-17	D:17.7" H:3"	15/25/32	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1950/3250/4160
RFUP-18	D:17.7" H:5"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1950/3250/4550

Options

EMG – Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com