



Properties

Base Construction	—
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	3000K

Finish Options

- | | |
|---|--------------------------------|
| ☐ Black | ☐ ORB |
| ☐ Brushed Nickel | ☐ White |
| ☐ Gold/Brass | |

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BCR-12	W:5.5" H:12"	6/10	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	780/1300
BCR-16	W:6.5" H:16"	9	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1170
BCR-20	W:7.5" H:20"	14	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1820

Not seeing what you're looking for?

Contact us!

info@asllighting.com