



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | —              |
| Lens              | Acrylic        |
| Application       | Sconce         |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Black              |
| CCT     | 3000K              |

### Finish Options

- Black
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size   | Dimensions           | Wattage | Voltage   | Lumens   |
|--------|----------------------|---------|---|----------|
| BCR-12 | H:12" W:5.5"<br>E:5" | 6/10    | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 780/1300 |
| BCR-16 | H:16" W:6.5"<br>E:6" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1170     |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)