







Properties	
Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	_
Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
<b>CCT Options</b>	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCRA-12	W:6" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
BCRA-16	W:6" H:16"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BCRA-20	W:6" H:20"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BCRA-24	W:6" H:24"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250

CCT

**Options** 

EMG – Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com