



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Acrylic        |
| Application       | Sconce         |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

### Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size     | Dimensions | Wattage | Voltage                                                                                                           | Lumens    |
|----------|------------|---------|-------------------------------------------------------------------------------------------------------------------|-----------|
| BCRBA-12 | W:6" H:12" | 10/15   | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950 |

### Options

EMG – Emergency  
 OS - Occupancy Sensor  
 OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)