



ADA Compliant

### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	ORB
CCT	3000K

### Finish Options

- |   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

### CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
BCRG-15	W:5" H:15"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
BCRG-24	W:5" H:24"	10/15/23	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2990

### Options

EMG – Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)