



ADA Compliant

## Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Frosted Glass     |
| Application       | Sconce            |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

## Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

## Finish Options

|   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

## Options

| Size   | Dimensions   | Wattage | Voltage   | Lumens |
|--------|--------------|---------|---|--------|
| BRA-10 | W:7.2" H:10" | 15      | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950   |

## Options

EMG – Emergency  
OS - Occupancy Sensor  
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)