









Properties

□ Bronze

CCT

☐ Brushed Nickel

CCT Options

Properties	
Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	ORB
CCT	3000K
Finish Options	
□ Black	☐ Gold/Brass

□ ORB

□ White

Options

Size	Dimensions	Wattage	Voltage	Lumens
BSK-15	W:9" H:15"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-18	W:9" H:18"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-26	W:9" H:26"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

Options

EMG – Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming Not seeing what you're looking for?

2700K/3000K/3500k/4000K/5000K

Contact us!

info@asllighting.com