



## Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## Standard Selection

Voltage	120V (non dimming)
Finish	ORB
CCT	3000K

## Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> Gold/Brass
<input type="checkbox"/> Bronze	<input type="checkbox"/> ORB
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> White

## CCT Options

CCT	2700K/3000K/3500K/4000K/5000K
-----	-------------------------------

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BSK-15	W:9" H:15"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-18	W:9" H:18"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-26	W:9" H:26"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

## Options

EMG – Emergency  
OS - Occupancy Sensor  
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)