



Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	ORB
CCT	2700K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	2700K/3500k/4000K/5000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BSK-15	W:9" H:15"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-18	W:9" H:18"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BSK-26	W:9" H:26"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

Options

- EMG – Emergency
 OS - Occupancy Sensor
 OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com