









# **Properties**

Base ConstructionSteelLens—ApplicationSconceLocationDampCRI80Life Hours50,000Light SourceIntegrated LED		
Application Sconce Location Damp CRI 80 Life Hours 50,000	Base Construction	Steel
Location Damp CRI 80 Life Hours 50,000	Lens	_
CRI 80 Life Hours 50,000	Application	Sconce
Life Hours 50,000	Location	Damp
	CRI	80
Light Source Integrated LED	Life Hours	50,000
	Light Source	Integrated LED

# **Standard Selection**

120V (non dimming)	Voltage
Antique Bronze	Finish
3000K	CCT

# **Finish Options**

☐ Antique Bronze

### **CCT Options**

CCT

2700K/3000K/3500k/4000K/5000K

### Options

Size	Dimensions	Wattage	Voltage	Lumens
CCS6-11	W:11.75" H:11"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/3250

#### **Options**

EMG – Emergency
OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com