



ADA Compliant

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black/Gold
CCT	3000K

Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> ORB
<input type="checkbox"/> Bronze	<input type="checkbox"/> White
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> Black/Gold
<input type="checkbox"/> Gold/Brass	

CCT Options

CCT	2700K/3000K/3500K/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
CCS36-12	W:6" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
CCS36-15	W:6" H:15"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600

Options

EMG – Emergency
 OS - Occupancy Sensor
 OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com