



Properties

| | |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Frosted Glass |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- | | |
|---|-------------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White |

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|--------------------------|----------|---|--------|
| ODTA-16 | H:9.8" W:16.5" E:4.7" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com