



ADA Compliant

Properties

| | |
|-------------------|----------------|
| Base Construction | Aluminum |
| Lens | Glass |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | GRAY |
| CCT | 3000K |

Finish Options

| | |
|---|--------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> White |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> GRAY |
| <input type="checkbox"/> Gold/Brass | |

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|------------|---------|---|--------|
| STPV1-3 | W:3" H:5" | 3 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 390 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com