







Properties

Е	Base Construction	Cold-rolled Steel
L	ens	Acrylic
P	Application	Sconce
L	ocation	Damp
C	CRI	80
L	ife Hours	50,000
L	ight Source	Integrated LED
L	ight Direction	UP AND DOWN

Standard Selection

Standard Selection					
Voltage	120V (non dimming)				
Finish	White				
ССТ	3000K				
Finish Options					
□ Black	☐ Gold/Brass				
□ Bronze	□ ORB				

CCT Options

☐ Brushed Nickel

CCT 2700K/3000K/3500k/4000K/5000K

 $\ \square$ White

Options

Size	Dimensions	Wattage	Voltage	Lumens
TLBF-10	W:9.8" H:4.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
TLBF-12	W:12" H:3.5"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
TLBF-24	W:24" H:3.5"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
TLBF-36	W:36" H:3.5"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900

Options

OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com