









## **Properties**

	Base Construction	Steel
	Lens	Acrylic
	Application	Sconce
	Location	Damp
	CRI	80
	Life Hours	50,000
	Light Source	Integrated LED
	Light Direction	UP AND DOWN

## Standard Selection

otandard ociection					
Voltage	120V (non dimming)				
Finish	Brushed Nickel				
CCT	3000K				
<b>Finish Options</b>					
□ Black	☐ Gold/Brass				

□ ORB  $\square$  White

## **CCT Options**

☐ Brushed Nickel

□ Bronze

CCT 2700K/3000K/3500k/4000K/5000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
TLBF-10	W:9.8" H:4.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
TLBF-12	W:12" H:3.5"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
TLBF-24	W:24" H:3.5"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
TLBF-36	W:36" H:3.5"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900

Options

OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming Not seeing what you're looking for?

Contact us!

info@asllighting.com