









Properties

	Base Construction	Steel
	Lens	Acrylic
	Application	Sconce
	Location	Damp
	CRI	80
	Life Hours	50,000
	Light Source	Integrated LED

Standard Selection

120V Triac dimming	Voltage
Brushed Nickel	Finish
3000K	CCT

Finish Options

☐ Brushed Nickel

CCT Options

CCT 2700K/3000K/3500k/4000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
WQT-11	W:11" H:5.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQT-15	W:15" H:6.87"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQT-19	W:19" H:9.75"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

Options

OS - Occupancy Sensor

Not seeing what you're looking for?

Contact us!

info@asllighting.com