



## Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## Standard Selection

Voltage	120V Triac dimming
Finish	Brushed Nickel
CCT	3000K

## Finish Options

☐ Brushed Nickel

## CCT Options

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

## Options

Size	Dimensions	Wattage	Voltage	Lumens
WQT-11	W:11" H:5.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQT-15	W:15" H:6.87"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQT-19	W:19" H:9.75"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

## Options

OS - Occupancy Sensor

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)