









Properties

| | Base Construction | Steel |
|--|-------------------|----------------|
| | Lens | Acrylic |
| | Application | Sconce |
| | Location | Damp |
| | CRI | 80 |
| | Life Hours | 50,000 |
| | Light Source | Integrated LED |
| | | |

Standard Selection

| Voltage | 120V Triac dimming |
|---------|--------------------|
| Finish | N/A |
| CCT | 3000K |

Finish Options

□ N/A

CCT Options

CCT 2700K/3000K/3500k/4000K

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------|----------|---|----------------|
| WQTA-11 | W:11" H:5.5" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| WQTA-15 | W:15" H:6.87" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| WQTA-18 | W:18" H:9" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| WQTA-19 | W:19" H:9.75" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |

Options

OS - Occupancy Sensor

Not seeing what you're looking for?

Contact us!

info@asllighting.com