



### Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V Triac dimming
Finish	N/A
CCT	3000K

### Finish Options

N/A

### CCT Options

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
WQTA-11	H:5.5" W:11" E:3.87"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQTA-15	H:6.87" W:15" E:3.87"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
WQTA-19	H:9.75" W:19" E:3.87"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

### Options

OS - Occupancy Sensor

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)